

TECHNICAL DATA SHEET

VER. JANUARY 2024

HUZZAH PRO OCCP 1.6J edition WITH CHARGING CABLE (TYPE 2) 11 KW

HUZZAH is the compact EV / PHEV chargers series designed to ensure the highest safety standards. Thanks to its 45° integrated holder and spiraled charging cable with Type 2 connector the HUZZAH is an extremely less space-required solution. Perfect for the private and semi-public installations. The integrated DC fault current detector guarantees an extra high operation safety standard.



HUZZAH PRO is capable of dynamically adjusting the charge current, depending on other loads that use the same mains connection. It is also possible to charge the EV from solar power to send all generated power from solar panels to a charging car.

In addition, the OCCP 1.6J edition is available in versions with Ethernet or 4G cellular interfaces. The charging controller can communicate with a central management system via an OCPP interface (via OCPP 1.6J, JSON).

GENERAL INFO

Model	Huzzah Type 2
Version	PRO OCCP 1.6J edition
Packing dimensions (HxWxD)	425 x 520 x 180 mm
Packaging unit	1 unit
Components included	Wallbox, printed quick reference guide, drilling template, installation kit,

ELECTRICAL DATA

Rated voltage	380-440V ~ 3 phase
Rated current	16 A
Grid frequency	50/60 Hz
Power (standby)	< 5W
Recommended upstream fuse	25 A, C characteristic recommended
External power supply	5 x 2,5 m ²



Terminal blocks	Direct connection to terminal block (max 10 mm ²) PE: max. 10 mm ² feed-through terminal block
-----------------	--

VEHICLE DATA

Connection	Spiraled charging cable with Type 2 connector in acc. with IEC62196-2, 5m range
Output voltage	380-440V ~ 3 phase
Max. charging current	16A
Maximum output	11 kW

SAFETY FEATURES

DC fault current detection	$I_{\Delta n}$ d.c. ≥ 6 mA
Ground monitoring	Included
Load switching	SSR (Solid State Relay)
Overvolatge protection	Included
Temperature monitoring	Cool-down [©] system → active temperature monitoring, charging current reduction or shut down
Recomanded RCCB	RCCB 25A, Type A, 30 mA to comply IEC 60364-7-722

COMMUNICATION

Comunciation Charger-User	LED
Communication EV	In acc. with IEC 61851-1 Mode 3 / SAE J1772 compliant
Communication EVSE	Modbus RTU , Modbus/TCP, OCPP 1.6J, MQTT, REST-API
LAN/WAN	Ethernet
WBM	Web-based management (WBM) for configuration, diagnostics, and operation (dashboard)
4G cellular communication	micro SIM card slot (optional)
Authorization	RFID(optional)
Interfaces	microSD card slot, USB type C, 2 x Ethernet

ENCLOSURE

Mounting type	Wall-mounted or dedicated pedestal (option)
Material	Plastic
Housing color	RAL 9011
Cover color	Glossy Black
Locking mechanism	Lockable cover with integrated lock
Dimensions (H×W×D)	400 x 300 x 145 MM
Weight	5,5 kg

STANDARDS

IEC 61851-1

IEC 61851-22

IEC 60364-7-722

OPERATING CONDITIONS

Storage temperature	-30° to 70° C
Operating temperature	-30° to 70° C
Degree of protection (housing)	IP54 / IK10

DIMENSIONAL DRAWING

